24Gbps Active Optical HDMI Cable | 4K UHD 4:4:4/60 10-Bit HDR | ISF Certified

2m/6.5ft | 4m/13.1ft | 6m/19.6ft | 8m/26.2ft



Quickstart Guide

WyreStorm recommends reading through this document in its entirety to become familiar with the product's features prior to starting the installation process.









9m

10m

List of Products

EXP-CAB-HAOC-2	2m/6.5ft
EXP-CAB-HAOC-4	4m/13.1ft
EXP-CAB-HAOC-6	6m/19.6ft
EXP-CAB-HAOC-8	8m/26.2ft

In The Box

1x See List of Products 1x Reusable Cable Ties 1x Quickstart Guide (This Document)

Cable Distances

EXP-CAB-HAOC-2

Optical HDMI Cable Performance Guide 2m

0ft	3ft	6.5ft	10ft	13.1ft	16ft	19.6ft	23ft	26.2ft	30ft	33ft
Н	D/4K Tra	ansmissio	n							
EXP-	-CAB-	HAOC-	4							
Optica	al HDMI	Cable Per	forman	ce Guide						
0m	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m
Oft	3ft	6.5ft	10ft	13.1ft	16ft	19.6ft	23ft	26.2ft	30ft	33ft

EXP-CAB-HAOC-6


Ontical	HDMI	Cable	Performance	Guide

0m	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m
Oft	3ft	6.5ft	10ft	13.1ft	16ft	19.6ft	23ft	26.2ft	30ft	33ft
н	D/4K Tra	ansmissio	n							
EXP-	-CAB-	HAOC-	8							
Optica	al HDMI	Cable Per	forman	ce Guide						
0m	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m


0m	1m	2m	3m	4m	5m	6m	7m	8m	9m	10m
96	06	6.50	400	40.46	466	40.66	000	06.06	000	006
Oft	3ft ID/4K ⊤r∞	υ.5π ensmissio		13.1π	1611	19.6π	23π	26.2ft	30π	33ft

Basic Wiring Diagram

HD/4K Transmission









Note: Cable is unidirectional. Follow the connector labeling to ensure proper operation of the cable

Wiring and Connections



IMPORTANT! Installation Requirements

- Follow the labeling and the diagrams for connection to ensure proper
- Due to the core of the HAOC being fiber optic the cable cannot have a bend radius greater than 2cm/0.8in. Keep this mind when routing cables around objects and inside of walls.
- The cables have a max pull tension of 15kg/33lbs. Keep this in mind when routing the cable within cabinets or walls to avoid damaging the cable.



Warranty Information

WyreStorm Technologies LLC warrants that its products to be free from defects in material and workmanship under normal use for a period of two (2) years from the date of purchase. Refer to the Product Warranty page on wyrestorm.com for more details on our limited product warranty.



Specifications

Transmission							
Transmission Encoding	Uncompressed AOC						
End to End Latency	10µs						
Maximum Transmission Bit Rate	24 Gbps (4-core, 6Gbps per lane)						
Video							
HDMI	v2.0b) TMDS 600MHz Maximum	L (v2 1) FRL (Fixed R	ate Link) I 16h/18h en	acodina			
Input	1x HDMI: 19-pin type A Male	11 (V2.1) 1 112 (1 MCG 11					
Output	1x HDMI: 19-pin type A Male						
Maximum Data Rate	22.28 Gbps						
viaximum data nate	22.20 0003	EXP-CAB-	EXP-CAB-	EXP-CAB-	EXP-CAB-		
		HAOC-2	HAOC-4	HAOC-6	HAOC-8		
	1920 x 1080p @120Hz						
Video Poselution (Max)	2560 x 1440p @144Hz	01711100 400					
Video Resolution (Max)	3840 x 2160p @60Hz 10bit HDR 4 3840 x 2160p @60Hz 12bit HDR 4		4m/13.0ft	6m/19.6ft	8m/26.3ft		
	3840 x 2160p @60Hz 10bit HDR		1111/ 10.010	0111, 13.010	0111, 20.010		
	3840 x 2160p @60Hz 10bit HDR I						
0	5120 x 2880p @30Hz 10bit HDR		N LIDD1 LD0 LDT000	O L DT 0100			
Supported Standards	DCI RGB Static HDR HDR10+	Dolby Vision HLG S	SL-HUKT PQ BT.202	U B1.2100			
Audio	0.1.004144.19.1	TO VID "					
Audio Formats	2ch PCM Multichannel LPCM D	TS-X Dolby Atmos					
Maximum Sampling Rate	192KHz						
Maximum Audio Channels	32						
Audio Return Channel (ARC)	Supported						
Communication and Control							
HDCP	Pass-through, 2.3 Supported						
EDID	Pass-through, RX>TX						
Ethernet	100Mbps Supported						
Consumer Electronics Control (CEC)	Supported						
Auto Low Latency Mode (ALLM)	Supported						
Variable Refresh Rate (VRR)	Supported						
Installation Restrictions							
Max Bend Radius	2cm						
Max Pull Tension	15kg/33lbs						
Orientation	Uni-directional - Observe signal flo	ow direction prior to in	nstallation				
Power							
Power Supply	Passive 4.5v~5.5v VCC (From Co	nnected Source)					
Max Power Consumption	250mW						
Environmental							
Operating Temperature	14°F ~ 122°F (-10°C ~ 50°C) 10°	% ~ 90%, non-conden	sing				
Storage Temperature	-4°F to ~ 140°F (-20°C ~ +60°C)	10% ~ 90%, non-cond	densing				
Maximum BTU	0.85 BTU/hr						
Impact	Low, free from single use plastic						
Dimensions and Weight (Connector Ho	using)						
Height	9mm/0.36in						
Width	19.8mm/0.78in						
Depth	39.5mm/1.56in						
Weight	NA						
Cable Length	EXP-CAB-HAOC-2 EXP	P-CAB-HAOC-4	EXP-CAB-HAOC	-6 EXP-0	AB-HAOC-8		
(Connector to Connector)		13.0ft	6m/19.6ft	8m/26			
Regulatory	,						
Safety and Emission	CE FCC RoHS						

Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.