
WyreStorm Express[™] 3x1 HDMI Switcher with Remote EXP-SW-0301 v2







WyreStorm - Powerful. Reliable. Simple.

Introduction

The WyreStorm Essentials EXP-SW-0301 enables quick and easy auto-switching of up to three 4K HDR or 1080p HDMI sources to a single HDMI output with control from both the front panel or the IR remote handset included. The EXP-SW-0301 also upgrades to support the full 18Gbps bandwidth HDMI 2.0 offers; 2160p@60Hz 4:4:4 and support for Dolby Vision[™] included.

Key Features

- Simple plug-and-play connection no set up or software required
- Passive operation means power is drawn from connected devices, no external PSU required
- Allows up to 3 HDMI devices, such as satellite decoder or Blu-Ray player, to be switched to one HDMI display device
- Supports 4K@60Hz 10bit 4:2:0 | 4:4:4 and HDR@24Hz 10bit BT.2020
- Fully HDCP 2.2 compliant
- Data rates up to 18Gbps

In the Box

- 1x EXP-SW-0301 Switcher
- 1x Remote Control Handset (CR2025 Battery not Included)
- 1x IR Receiver Cable
- 2x Mounting Brackets

- Automatically negotiates EDID signals from display for seamless
 communication between devices
- HDR and Dolby Vision support
- DTS-X and Dolby Atmos[™] supported
- Plug and play set up for easy installation no set up / drivers / software required
- · Compact, durable design for unobtrusive installation

Specifications

Audio and Video			
Inputs	3x HDMI In: 19-pin type A		
Outputs	1x HDMI Out: 19-pin type A		
Output Video Encoding	HDMI TMDS		
Audio Formats	2ch PCM Multichannel: LPCM and up to DTS-X and Dolby Atmos		
Video Resolutions (Max)	Video Resolutions 1920x1080p @60Hz 12bit 1920x1080p @60Hz 16bit 3840x2160p @24Hz 10bit 4:2:0 HDR 3940x2160p @30Hz 8bit 4:4:4 3840x2160p @60Hz 10bit 4:2:0 HDR 4096x2160p @60Hz 8bit 4:2:0 4096x2160p @60Hz 8bit 4:4:4	HDMI 15m/49ft 7m/23ft 5m/16ft 7m/23ft 5m/23ft 7m/23ft 5m/16ft	
Color Depth	10bit		
Maximum Pixel Clock	297Mhz		
Communication and Control			
HDMI	HDCP 2.2 EDID DVI-D supported with adapter (not included)		
IR	1x Front Panel Sensor 1x IR Ext: 3.5mm (1/8in) TRS Stereo		
Power			
Power Supply	5V DC 1A (HDMI In External Power Supply)		
Max Power Consumption	0.25W		
Environmental			
Operating Temperature	0~+ 45°C (32~+ 113 °F), 10%~90%, non-condensing		
Storage Temperature	-20~+70°C (-4~+ 158 °F), 10%~90%, non-condensing		
Maximum BTU	0.85 BTU/hr		
Dimensions and Weight			
Rack Units	< 1U		
Height	21mm/0.83in		
Width	137mm/5.39in		
Depth	70.2mm/2.76in		
Weight	0.26kg/0.57lbs		
Regulatory			
Safety and Emission	CE FCC RoHS RCM		

Right Product for the Right Application.

