



High Brightness Short-Throw Projector

FEATURE

- Bright 3,600 ANSI lumens with a high 12,000:1 contrast ratio
- WXGA resolution with a maximum resolution up to WUXGA
- Delivers a 88" diagonal image from less than 1 meter installation distance from the surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- Assortment of connectivity options including HDMI 1.4b, VGA, S-Video, Composite Video, Audio-In/Out
- 3D compatibility with DLP® Link™ and HDMI 1.4b Blu-ray support for dazzling and realistic life-like images
- 6 Segments (RYGCWB) colorwheel for accurate and detailed images
- Sealed optical engine to keep dust out and improve performance
- Integrated 10W audio speakers
- Integrated network monitoring and management solutions (product certified) including Crestron® RoomView™, Extron, AMX SSDP and Telnet
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad



The DW882ST is designed to cater for the education needs. The DW881ST delivers a 88" diagonal image from less than 1 meter installation distance from the surface. With a brightness of 3,600 ANSI Lumens and contrast ratio of 12,000:1 it delivers a perfect image display. The projector is designed for use in any classroom, small office or at home. With its light weight and compact form this is a short throw projector for easy installation that will fit any budget.

DW882ST

EDUCATION



SPECIFICATIONS



Display Type	Single 0.65" DLP Technology by TI
Brightness	3,600 ANSI Lumens
Native Resolution	WXGA (1280x800)
Maximum Resolution	WUXGA (1920x1200)@60Hz
Contrast Ratio	12,000:1
Lamp Life and Type	3500h/5000h/7000h, UHP Osram 240W/190W (Normal/Eco/Dyn. Eco)
Throw Ratio	0.52
Image Size (Diagonal)	68" ~ 200"
Projection Distance	0.77 ~ 2.24
Projection Lens	F2.8, f=7.51mm
Zoom Ratio	Fixed
Aspect Ratio	16:10 Native
Offset (full image height)	112% (full image height)
Keystone Correction	+/-40 Degree; +/- 40 Steps
Horizontal Frequency	15, 31 - 91Hz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Lens Shift Range	n/a
3D Compatibility	Yes (DLP® Link™, HDMI 1.4b (Blu-Ray))
Audio	10W (Mono)
Video Compatibility	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
I/O Connection Ports	HDMI v1.4b, VGA-In (x2), S-Video, Composite Video, Audio-In (Mini-Jack)(x3), VGA-Out, USB (Type A for 5V/1.5A Power Only), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service), Microphone (Mini-Jack), 12V Trigger
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (WxDxH)	314 x 216 x 126 mm
Weight	3.2kg
Noise Level	36dB/32dB (Normal/Eco. Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 310W (Normal Mode), <0.5W (Standby Mode)
Standard Warranty	3 years projector / 1 year on lamp or 1000 hours whichever comes first
Education Warranty	5 years projector / 3 years on lamp or 2000 hours whichever comes first
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Lens Cap, Documentation Kit
Optional Accessories	Replacement Lamp: 5811119560-SVV
UPC	814964 339843

© Copyright 2014 Vivitek. Vivitek is a registered trademark of Delta Electronics, Inc.

DLP® and the DLP logo are registered trademarks of Texas Instruments. All specifications are subject to change at any time.

Vivitek EMEA, Zandsteen 15, 2132 MZ Hoofddorp, The Netherlands

tel: +31 20 655 0960 | fax: +31 20 655 0999 | email: info@vivitek.eu