

**MULTIMEDIA
PROJECTOR**

DX864



XGA Projector with Embedded Media Player

Vivitek's multimedia ready DX864 high-performance digital projector offers exceptional digital images with full color saturation. The projector features native XGA resolutions, multiple connectivity options and a brightness up to 3,500 ANSI Lumens. The embedded media player enables to play MS documents, photos, videos and audio files, all without being connected to a PC. The projector can wirelessly display content from a PC/Mac, by connecting the optional WiFi dongle. The DX864 is ideal for just about any multimedia/video application. Great functionality, high performance and excellent value for money, all found in the Vivitek DX864 projector.

Features

- 3,500 ANSI Lumens of brightness with a 6000:1 contrast ratio
- XGA (1024 x 768) resolution with a maximum resolution up to UXGA (1600 x 1200)
- DLP[®] and BrilliantColor[™] technologies from Texas Instruments
- Integrated media player MS-office viewer conveniently displays documents, photos, videos and audio files without the need to connect a PC
- WiFi, LAN and USB display functions allow the projector to display from any PC/MAC
- Assortment of connectivity options for easy connection to a variety of multimedia devices (HDMI, VGA, USB)
- Built-in 10W loudspeaker
- Crestron[®] RoomView[™] integration for network monitoring and management
- Sealed optical engine, minimizing the impact of dust and smoke
- Ani-theft security features include: Kensington[®] security slot, security bar, and PIN lock keypad

Product Pictures



| Specifications | | |
|------------------------|--|--|
| Display Type | Single 0.55" DLP Technology by TI | |
| Brightness | 3,500 ANSI Lumens | |
| Native Resolution | XGA (1024 x 768) | |
| Maximum Resolution | Up to UXGA (1600 x 1200)@60Hz | |
| Contrast Ratio | 6,000:1 | |
| Lamp Life/Type | 5000 / 3500 hours (Eco / Normal mode), 240W / 190W | |
| Throw Ratio | 1.6 - 1.92:1 | |
| Image Size (Diagonal) | 25.6" - 308" | |
| Projection Distance | 1 - 10m | |
| Projection Lens | F#2.50-2.72, f=17.81-22.35mm | |
| Zoom Ratio | 1.2x | |
| Aspect Ratio | 4:3 Native | |
| Offset | 114% (UIS) / 128% | |
| Keystone Correction | Vertical +/-15 Degree | |
| Horizontal Frequency | 15, 30 ~ 91.4kHz | |
| Vertical Scan Rate | 43 ~ 87Hz | |
| Lens Shift Range | N/A | |
| 3D Compatibility | Yes | |
| Audio | 10W | |
| File Formats Supported | Documents | Microsoft [®] Office 97 - 2007 (DOC, PPT, XLS), Adobe [®] Reader (PDF), Text (TXT) |
| | Video | AVI, DIVX, MKV, TS, DAT, VOD, MPG, MPEG, MOV, MP4, RM, RMVB, WMV |
| | Image | JPEG, JPG, BMP |
| | Audio | MP1, MP2, MP3, WMA, OGG, ADPCM-WAV, PCM-WAV, AAC |
| Video Compatibility | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) | |
| I/O Connection Ports | HDMI v1.3, VGA-In (x2), Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), VGA-Out, USB (Type A)(x2), Audio-Out (Mini-Jack), RJ45, RS-232C, Mini-USB (Service) | |
| Projection Method | Table Top, Ceiling Mount (Front or Rear) | |
| Security Solutions | Kensington [®] Security Slot, Security Bar, Keypad Lock | |
| Dimensions (WxDxH) | 285 x 261 x 121.8mm | |
| Weight | 3.15kg | |
| Available Color | White | |
| Noise Level | 35dB/32dB (Normal/Eco Mode) | |
| Power Supply | AC 110-240V, 50/60Hz | |
| Power Consumption | 250W (Eco. Mode), 310W (Normal Mode), <0.5W (Standby Mode) | |
| Standard Accessories | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Lens Cap, Documentation Kit | |
| Optional Accessories | Wi-Fi USB Dongle, Replacement Lamp, Remote, Carrying Case | |
| Lamp P/N | 5811118543-SVV | |
| Warranty | 3 years projector / 1 year on lamp or 1000 hours whichever comes first | |
| UPC | 814964 339201 | |

